



ATI 500 - Specifications



Temperature	77°C / 171°F
BTU's	600,000
CFM	6000
Fuel Consumption P/Hr	4.2 Imp Gal / 19 L
Fuel Capacity	200 Imp Gal / 757 L
Weight (empty)	2,370 Lbs
Weight (full)	3,770 Lbs
Height	6'0"
Width	5'6"
Length	12'9"

BENEFITS

- Self Contained
- Portable
- EUB Approved / Working up to 7 Meters from the Wellhead
- Proven Results with Alberta Research Council
- Green Breathable Heat
- Allows Work to Occur Simultaneously
- Increased Engine Longevity
- Property Protection
- Reduce Costs from Reduced Timelines
- Double Containment Available Upon Request and Availability

APPLICATIONS

- Construction Sites
- Vessel / Tank Coat Curing
- Equipment & Ground Thawing
- Emergency & Facility Heating
- Well Head & B.O.P. Heating
- Health & Pest Control
- Plant Turnarounds/Start Ups
- De Humidifying / Drying
- Flood Clean Up
- Concrete Curing

PIONEERS IN FLAMELESS HEATING TECHNOLOGY

Rated 94% Efficient

* Efficiency rating is based off of ideal heating conditions and has a tolerance of +/- 3%

HEAD OFFICE

9502-87th Ave Morinville,
Alberta T8R 1K6
(780) 939.3141
info@artictherm.com

Drayton Valley

Whitecourt
Grande Prairie
Fort St. John



ARTIC THERM
International Ltd.
AN ENTERPRISE GROUP COMPANY

Toll Free: 1-855-350-HEAT (4328)

artictherm.com